

					<b>2枚刃 標準</b>  <b>CDMマルチ90° /60° /120°</b>		<b>2枚刃 標準</b>  <b>NEW</b> <b>ポジションドリルZ</b>			
										
										
先端角	刃径 d	刃長 ℓ	全長 L	シャンク D	型番	価格	※1	型番	価格	
A ± 1°	0~ -0.02	0~ +0.5	±0.5	h6						
	90°	3.0	6	50	φ4	CDM 090030 F/E	3,080			
		4.0	8	50	φ6	CDM 090040 F/E	3,910	ℓ12 D4	PDST 040900 ZrN	2,080
		6.0	12	60	φ8	CDM 090060 F/E	6,550	ℓ20 D6	PDST 060900 ZrN	2,470
		8.0	16	75	φ10	CDM 090080 F/E	8,580	ℓ25 L60D8	PDST 080900 ZrN	4,670
		10.0	20	75	φ12	CDM 090100 F/E	9,410	ℓ25 D10	PDST 100900 ZrN	6,780
		12.0	25	75		CDM 090120 F/E	9,410	ℓ25 D12	PDST 120900 ZrN	9,760
		16.0	32	100	φ16	CDM 090160 F/E	20,070	※1左記寸法との差がある点 ℓ 刃長 L全長 Dシャンク径		
20.0		35	100	φ20	CDM 090200 F/E	24,730				
60°	6.0	12	60	φ8	CDM 060060 F/E	6,930				
	8.0	16	75	φ10	CDM 060080 F/E	9,130				
	10.0	20	75	φ12	CDM 060100 F/E	10,010				
	12.0	25	75		CDM 060100 F/E	10,010				
120°	6.0	12	60	φ8	CDM 120060 F/E	6,930	ℓ20 D6	PDST 060120 ZrN	2,470	
	8.0	16	75	φ10	CDM 120080 F/E	9,130	ℓ25 L60D6	PDST 080120 ZrN	4,670	
	10.0	20	75	φ12	CDM 120100 F/E	10,010	ℓ25 D10	PDST 100120 ZrN	6,780	
	12.0	25	75		CDM 120100 F/E	10,010	ℓ30 D12	PDST 120120 ZrN	9,760	
・ピンク枠はNAKA推し					※刃径<シャンク径で剛性が高い。 先端部分0~0.1で且つセンター部 精度が高く、センタリング面取り、 面取りV溝加工に対応。		※刃径=シャンク径 先端部分0~0.1で且つセンター部 精度が高く、超硬ドリル用120° センターに最適			